HP DesignJet HD Pro 2 44-in MFP



High-definition graphics 44-in MFP for technical and graphics applications—fast and secure



PRECISE—Excellent reproduction with CCD technology

- Reproduce colors with excellent accuracy with CCD technology that enables high-quality color scanning/copying.
- Efficiently handle complex images with an advanced five-camera system that captures detail in high precision.
- Scan maps, orthophotos, and technical drawings
 —even if old and damaged—with CCD technology for great results.
- Create large-format color and black-and-white scans up to 42-in (1067-mm) wide on thick¹, rigid media.

FAST—HD scanner designed to streamline workflows

- Scan fast—up to 13 inches (33 cm) per second in either color or monochrome
- Accelerate workflows. Save scans as PDF, TIFF, JPEG, or DWF files. Do batch scanning. Create multipage PDFs.
- Scan to email, USB, network—or print with the HP DesignJet Z6dr 44-in PostScript[®] Printer with V-Trimmer.
- Work comfortably with a 15.6" (396-mm) color touchscreen.

SECURE—Protect your work and your information

- Protect printers/data from unauthorized access with HP Secure Boot, whitelisting, 500 GB encrypted hard disk.
- Protect documents, preserve confidentiality with authentication solutions like PIN printing, card readers.²
- Secure your printer with HP JetAdvantage Security Manager; manage your fleet remotely with HP Web Jetadmin.
- Reliable color—HP Professional PANTONE® color emulation, embedded Adobe® PostScript®, Adobe® PDF Print Engine.

For more information, please visit http://www.hp.com/go/DesignJet-HD-Pro-2-MFP

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

¹ Up to 0.6-in (15-mm) thickness.

² Card reader functionality enabled through optional third-party solutions.

Technical specifications

Normal 2017 (Pith or coloration delia Sect. 10 (Pith Viron or plays precised by Sect. 10 (Pith Viron or Plays prec	Print	Fort Forested and one for the land of the second of the se
Rechnology 149 Thermal Inligit Margins Roll Experiences on all media with V-Tironmer? Roll Experiences on all media with V-Tironmer? Sheet 0.22 of 15 x 17 x 5 x 5 mm) Pinters and Control of 17 x 3 duals of 17 x 5 x 5 mm) Pinters and Control on a significance of sheal for all colors? Pinters and Control on a significance of sheal for all colors? Pinters and Control on a significance of sheal for all colors? Pinters and Control on 3 index 63 minked Control on 13 index 63 minked Control on 14 index 64 minked Polit Polifia. The F, Pinto, PicG. 2000, DMF, CALS 08801, multi-page PDF generation Scan desirations File, minto USB HOU, network folder, FTB print Thickness Ob 6 in C15 minters of the control on 14 index 64 minters on 14 index 64 minters of the control on 14 index 64 minters of the control on 14 index 64 minters on 14 index 64 minter	Print speed	
Regions Roll, Bedreless on all models with VTiromore' Shell, Care AF A Care Na Chin S at 78 x 5 5 mm) Shell Cape Shell Care AF A Care Na Chin S at 78 x 5 5 mm) Ink Oppes Pigment-based 77 pa dual-deep weight API, C. PC, 6 pt single-drop weight Cr. CR, MIG Printheads 3 universal printheads (solid for all colors) Printheads Color: Up to 13 in/lace (33 em/lace) Color: Up to 13 in/lace (33 em/lace) Grapade up to 13 select (33 em/lace) Grapade up to 13 select (33 em/lace) Grapade up to 13 select (33 em/lace) Grapade up to 13 em/lace (33 em/lace) Grapade up to 14 em/lace (34 em/lace) Grapade up to 15 em/lace (34 em/lace) Grapade up to 14 em/lace (34 em/lace) Grapade up to 13 em/lace (34 em/lace)	Print resolution	Up to 2400 x 1200 optimized dpi
Sheet 0.2 x 0.67 x 0.2 x 0.2 x 1.6 x 1.7 x 5 x 5 mm) kit yapps Pigment based Nik drop 7/3 pt dual-drop weight CM, C, POS, 6 pt single-drop weight (Y, CR, MX) Printheads 3 universal printheads (social colors) Printhead mozales 2/11 2 per color. 126/2 bit total 2/11 2 per color. 126/2 bit total Post printhead mozales 2/11 2 per color. 126/2 bit total 1200 dpi Scan resculation 1200 dpi Scan resculation 1200 dpi CCD scanning technology and LED-based illumination system 1200 dpi CCD scanning technology and LED-based illumination system Scan format POS POR/A, TRE, PEGS, PEGSCOOD, DWK, CALS (StaW), multi-page PDF generation Scan format POS POR/A, TRE, PEGS, PEGSCOOD, DWK, CALS (StaW), multi-page PDF generation Scan format Post post post post post post post post p	Technology	HP Thermal Inkjet
ink drop 7/3 pl dual-drop weight (M.C. PRJ. 6 pl single-drop weight (M.C.R. MO) Printheads 3 universal printheads (would for all colors) Printhead rozales 2 112 per color (1.527 pl single-drop weight (M.C.R. MO) Multifunction capabilities Scan speed Color (Up to 13 in/sec (33 cm/sec) Color (Up to 13 in/sec (33 c	Margins	
Printheads 3 universal printheads (valid for all colors) Printhead nozides 2 112 per color; 12.67 2 in total Multifunction applitties Scan speed Goder Up to 13 infect G3 cm/sed Gasociale up 12 infection CD scanning technology and LED-based illumination system Scan destinations File, email, USB, 1600, network folder, FTR print. Thickness 0.6 in 15 mml File meal, USB, 1600, network folder, FTR print. Thickness 0.6 in 15 mml File meal USB, 1600, network folder, FTR print. Thickness 0.6 in 15 mml File meal USB, 1600, network folder, FTR print. Thickness 0.6 in 15 mml File meal USB, 1600, network folder, FTR print. Thickness 1.1 in 46-in 16 in	Ink types	Pigment-based
Printhroad nozaties 2112 per color; 12,672 in total Matifiantition capabilities Scan speed Ciriler by in 13 infect (33 cm/seq) Grapscale: up to 13 infect (33 cm/seq) Grapscale: up to 13 infect (33 cm/seq) Technology CD scanning technology and LED-based illumination system CD scanning technology and LED-based illumination system PDP PDF/A. THE, PSEC, PSEC2000, DMF, CR4, SBW/, multi-page PDF generation Scan destinations File, email, USB, HOD, network folder, FTB print Thickness OB 5115 rmm) Printer: Two automatic roll feeds, smart roll-switching, top sheet feed, media output bin, automatic horizontal cutter and vertic transmer (outs all HP 2-series printer-apallifer of media including most cannots) Scanners Table in through Scanners and page path for sheet, and cardioband dirights, adjustable pager pressure for very thin media. Face-down, front entry, roar eat, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originate up to 15 mm (05 ml thickness). 11 to 44-In (279 to 1118-mm) Standard sheets A, B, C, D, E Standard sheets A, B, C, D, E Thickness Up to 31.5 mill Barners, Exhibition and event graphics; Light boxes - film, Maps; Orthophotos; Point of sale/display, Posters Memory Printer: 120 GB (Bits-processings ¹⁵ , Scanner; B GB Hand disk Printer: SDO GB self-encrypting; Scanner; B GB Printer: SDO GB self-encrypting; Scanner; B GB GB Printer: SDO GB self-encrypting; Scanner; B GB GB Printer: SDO GB Self-encrypting; Scanner; B GB GB CB CB CB CB CB CB CB	Ink drop	7/3 pl dual-drop weight (M, C, PK); 6 pl single-drop weight (Y, CR, MK)
Color: Up to 13 in/sec (33 cm/sec)	Printheads	3 universal printheads (valid for all colors)
Color Lip to 13 injube: G3 cm/sec Color Lip to 13 injube: G3 cm/sec Color Color 1 Color Color to 1 Color Color to 1 Color Color Color to 1 Color	Printhead nozzles	2112 per color; 12,672 in total
Grayscales up to 13 in/sec (33 cm/sec) ³ Technology CD Scarning technology and LED-based illumination system Por PDFA, THE, PSEC, PSEC (2000, DMF, CALS (BRW), multi-page PDF generation Scan format Por PDFA, THE, PSEC, PSEC (2000, DMF, CALS (BRW), multi-page PDF generation Scan destinations File, email, USB, HDD, network folder, FTB, print Thickness O6 in 15 mill Media Handling Printer Two automatic cult finds, smart roll switching, top sheet feed, media output bin, automatic horizontal cutter and vertic primer (ora; oil HP 2-soile) printer-qualified media ficklading most cannels Scanners Straight through some paper path for sheet and corbound originals, adjustable page pressure for very thin media, Face-down, frost entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for fritisk originals up to 15 mm (05 in) thickness. 11 to 44+in (279 to 1118-mm) Standard sheets A, B, C, D, E Thickness Up to 31,5 mil Applications Barners; Exhibition and event graphics; Light boxes - Rim, Maps, Orthophotos; Point of safeldisplay, Posters Memory Printer: 128 GB (Ris-processings)*, Scanners GB GB Cornectivity Printer: 128 GB (Ris-processings)*, Scanners GB GB Cornectivity Printer: Rogable Ethernet (1000 Base-1), H-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigable Ethernet (1000 Base-1), H-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigable Ethernet (1000 Base-1), H-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigable Ethernet (1000 Base-1), H-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigable Ethernet (1000 Base-1), H-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigable Ethernet (1000 Base-1), H-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigable Ethernet (1000 Base-1), H-Speed USB 2.0 certified interface for dire	Multifunction capabilities	
Technology CCD scanning technology and LED-based illumination system POP, POPER, THE, PEEC, PEECODO, DWF, CLS (BRW), multi-page PDF generation POP, POPER, THE, PEEC, PEECODO, DWF, CLS (BRW), multi-page PDF generation PORTON CONTROL (ST. 1972) Porton Standard (St.	Scan speed	
Scan format PDF, PDF/R, TIFF, JPEG, JPEG2000, DWF, CALS (B8W), multi-page PDF generation File, email, USB, HDD, network folder, FTP, print Pitickness O. Sin (15 mm) Media Handling Printer: Two automatic roll feeds, smart roll-switching, too sheet feed, media output bin, automatic horizontal cutter and vertice frimmer (cuts all HP Z-series printer-qualified media, including most, amous) Scanner: Straight-Hrough Scan page that for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, from entry, ree ret, reund to from L-ve document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (D.6 in) thickness. Roll size 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) Standard sheets A, B, C, D, E Thickness Up to 315 mil Applications Banners; Exhibition and event graphics; Light boxes - film, Maps; Orthophotos; Point of sale/display; Posters Memory Printer: 128 GB (file-processing)** Scanner: 8 GB Hand disk Printer: 26 GB (Bite-processing)** Scanner: 8 GB Hand disk Printer: Glogabit Ethernet (1000Base-1), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-1), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-1), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-1), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-1), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-1), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-1), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-1), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigab	Scan resolution	1200 dpi
Scan destinations File, email, USB, HDD, network folder, FTIP, print Thickness O. 6 in (15 mm) Media Handling Printer: Two automatic roll feeds, smart roll-switching, top sheet feed, media output bin, automatic horizontal cutter and vertice trimmer (cuts all IMP 2-series printer-qualified media, including most canwas) Scanners: Straight-Privolys bard pape peath for sheet and carboard originsk, adjustable paper pressure for very thin media. Face-down, front entity, rear eed, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bloghe for thick originals by 10 15 mm (05 mil hitchress.) 11 to 44 in 1279 to 1118-mm) Sheet size 8.3 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) Standard sheets A. B., C. D. E Thickness Up to 3.1.5 mil Applications Banners: Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory Printer: 128 GB (file-processing)*, Scanner: 266 GB Connectivity Interfaces Printer: Gigabit Ethernet (1000Base-1), H-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: 266 GB Connectivity Interfaces Printer: Gigabit Ethernet (1000Base-1), H-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: 266 GB Connectivity Interfaces Printer: Raster and PostScript drivers for Windows and mac/S Por driver for Windows 8 and above Scanner: Windows 6 where for windows 8 and above Scanner: Windows 6 where for windows 8 and above Scanner: 10 x 37 x 65 m (1530 x 330 x 1660 mm) Printer: Printer: 20 x 27 x 4 x 65 m (1530 x 330 x 1660 mm) Printer: Printer: 211 Ib (96 kg) Scanner: 157 Ib (71 kg) Shipping 511 Ib (232 kg) What's in the box Printer: HD EssignJet Zedr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spinde, 3-in core adaptic, quick reference guide, setup poster, poster, oral Scrain (1940 x 1940 x 19	Technology	CCD scanning technology and LED-based illumination system
Media Handling Piriter: Two automatic roll feeds, smart roll-switching, top cheef feed, media output bin, automatic horizontal cutter and vertic rimmer (ruts all IMP Zearles printing authorizing, top cheef feed, media output bin, automatic horizontal cutter and vertic rimmer (ruts all IMP Zearles printing authorizing authorizing consultations). Scanners Straight-through Scanners Straight-through Scanners Straight-through Scanners Protection (principal), adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Roll size 11 to 44 in (279 to 1118 mm) Sheet size 8.3 x 11 to 44 x 66 in (2.0 x 279 to 1118 x 1676 mm) Standard sheets A. B. C. 0. E Thickness Up to 31.5 mil Applications Banners, Exhibition and event graphics; Light boxes - film; Maps; Onthophotos; Point of sale/display; Posters Memory Printer: 500 GB self-encrysting; Scanner: 8 GB Connective) Interfaces Printer: Gigabit Ethernet (1000Base-1), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-1), USB 3.1 gen 1 (3 + 1) and USB 2.0 (1) mear Native print tlanguages Adobe Post-Script 3, Adobe Post-Script 4 miles for Windows and macOS Dinersions (W x D x H) Printer: 70 9 x 27 4x 39.3 in (1802 x 695 x 998 mm) Scanner: 60 x 37 x 65 in (1530 x 390 x 1660 mm) Weight Printer: 20 1 b (96 kg) Scanner: 157 lb C7 lb (95 kg) Scanner: 157 lb C7 lb (95 kg) Scanner: 157 lb C7 lb (96 kg) Scanner: 157 lb (7 lb (96 kg) Scanner: 157 lb (7 lb (96 kg) Scanner: 158 lb (96 kg) Scanner: 158 lb (96 kg) Scanner: 159 lb (96	Scan format	PDF, PDF/A, TIFF, JPEG, JPEG2000, DWF, CALS (B&W), multi-page PDF generation
Heading Printer: Two automatic roll feeds, smart roll-switching, top sheet feed, media output bin, automatic horizontal cutter and vertice trimmer (ruts all HP Z-series printer-qualified media, including most canvas) Scanners Straight-Hhough scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rese valt, rewind for front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness. Roll size 8.3 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) Sheet size 8.3 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) Sheet size 8.3 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) Sheet size 8.3 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) Sheet size 9. x 12 to 13.5 mll Applications Banners; Eshibition and event graphics; Light boxes - film; Maps; Onthophotos; Point of sale/display; Posters Memory Printer: 128 GB (file-processing) ⁶ ; Scanner: 8 GB Hand disk Printer: 500 GB self-encrypting; Scanner: 256 GB Connectivity Interfaces Printer: Gigabit Ethernet (1000Base-1), H-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-1), USB 3.1 gen 1 (3 + 1) and USB 2.0 (1) rear Notive print languages Adobe PostScript 3, Adobe Pol 1, 7, 17E, 17E, 6CA, Sci 4, Pe. GAL, Sci 4, Pe. GAL, Pe. RTL Drivers Printer: Raster and PostScript drivers for Windows and macOS POF driver from Windows devel or compatible HP PageWide XL and HP Designalet Printers Dimensions (W x D x H) Printer Printer: 7.0 x 2.7 x 3.3 x 3 in (1802 x 565 x 998 mm) Scanner: 6.0 x 37 x 65 in (1530 x 930 x 1660 mm) Shipping 7.7 x 3.0 x 50 in (1950 x 766 x 1260 mm) What's in the box Printer: HP Designalet Z6d 44 in PostScript Printer with V-Termers printheads, introductory ink cartridges, printer stand and media lain, spidio: 3. in orce adapter, quick reference quide, estip poster, power cord, Scanner: HP HD Prio 2 42-in Scanner, Stan tourb.creen panel PD. q	Scan destinations	File, email, USB, HDD, network folder, FTP, print
Handling Printer: Two automatic roll feeds, smart roll-switching, top sheet feed, media output bin, automatic horizontal cutter and vertice trimmer (cuts all IP Z-series printer-qualified media, including most canves). Scamers: Straight: through son paper path for sheet and carbooard organis, adjustable paper pressure for very thin media. Fase-down, front entry, rear east, rewind to front, use the and carbooard organis. Adjustable paper pressure for very thin media. Fase-down, front entry, rear east, rewind to front, use document return guide for front-return. Automatic high adjustment of scamers bridge for thick organises up to 13 mm (Lis document return guide for front-return. Automatic high adjustment of scamers bridge for thick organises up to 13 mm (Lis document return guide for front-return. Automatic high adjustment of scamers bridge for thick organises up to 13 mm (Lis document return guide for front-return. Automatic high adjustment of scamers bridge for thick organises up to 13 mm (Lis document return guide for front-return. Automatic high adjustment of scamers bridge for the large for form (Lis document). Applications Banners: Exhibition and event graphics; Light bowes - film, Maps; Orthophotos; Point of sale/display; Posters Printer: 1506 GB Beelf-encrypting; Scamers: 256 GB Connectivity Interfaces Printer: 1506 GB Beelf-encrypting; Scamers: 256 GB Connectivity Interfaces Printer: Gigabit Ethernet (1000Base-17), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scamer: Gigabit Ethernet (1000Base-17), USB 3.1 gen 1 (3 + 1) and USB 2.0 (1) rear Native print languages Adobe PostScript 3, Adobe PDE 1.7, TIFF, IPEG, CALS 6.4 IPEG/IZ_IPE-RIT. Drivers Printer: Gigabit Ethernet (1000Base-17), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scamers: Gb 37 x 65 in (1530 x 930 x 1660 mm) Printer: 70.9 x 27 x 4 33.3 in (1802 x 6	Thickness	0.6 in (15 mm)
trimmer (cuts all HP Z-series printer-qualified media, including most canwal) Scanners Straight-through scan paper path for shet and cardward drightals, adjustable paper pressure for very thin media. Face-down, front entry, rear ext, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in thickness.) Roll size 11 to 44-in (279 to 1118-mm) Sheet size 8.3 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) Sheet size 8.3 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) Sheet size Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display, Posters Wemony Printer: 128 GB (file-processing)*, Scanner: 8 GB Hard disk Printer: 200 GB self-encrypting; Scanner: 256 GB Connectivity Interfaces Printer: Gigabit Ethernet (1000Base-1), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-1), USB 3.1 gen 1 (3 + 1) and USB 2.0 (1) rear Native print languages Adobe PostScript 3, Adobe P0F 1.7, TIFF, IPEG, CALS G4, IPP-GL/Z, IPP-RTL Drivers Printer: Raster and PostScript drivers for Windows and macOS DPF driver for Windows as and above Scanner: Windows drivers for compatible IHP PageWide XL and IHP DesignJet Printers Dimensions (W x x x x) Printer: Pointer: 7.0.9 x 27.4 x 39.3 in (1802 x 695 x 998 mm) Scanner: 60 x 37 x 65 in (1530 x 930 x 1660 mm) Shipping 77 x 30 x 50 in (1950 x 766 x 1260 mm) Weight Printer: PIP DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bins, psindle, 3-in core adapter, quick reference guide, setup poster, power cord; Scanner: IHP IHD Pro 2 42-in Scanner, Stan touchscreen (panel PC), quick reference guide, media guides, setup poster, maintenance sheet, copy/scan software, documentation software, Ethernet etable, USB calde, power cord; Scanner: IHP IHD Pro 2 42-in Scanner, Stan touchscreen (panel PC), quick reference gui	Media	
Sheet size 8.3 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm) Standard sheets A, B, C, D, E Thickness Up to 31.5 mil Applications Banners; Exhibition and event graphics; Light boxes – film; Maps; Orthophotos; Point of sale/display; Posters Memony Printer: 128 GB (file-processing)*, Scanner: 8 GB Hard disk Printer: 500 GB self-encrypting; Scanner: 256 GB Connectivity Interfaces Printer: Gigabit Ethernet (1000Base-T), US9.3.1 gen 1 (3+1) and US9.2.0 (1) rear Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Drivers Printer: Raster and PostScript divers for Windows and macOS PDF driver for Windows 8 and above Scanner: Windows drivers for compatible HP PageWide XL and HP DesignJet Printers Dimensions (W x D x H) Printer Printer: 7.9 x 27.4 x 39.3 in (1802 x 695 x 998 mm) Scanner: 60 x 37 x 65 in (1530 x 930 x 1660 mm) Weight Printer Printer: 211 lb (96 kg) Scanner: 157 lb (71 kg) Shipping 511 lb (232 kg) What's in the box Printer: P DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in, core adapter, quick reference quide, setup poster, power cord; Scanner, HP HD Pro 2 42-in Scanner, stan touckscreen planel PC, quick reference quide, setup poster, power cord; Scanner, HP HD Pro 2 42-in Scanner, stan touckscreen planel PC, quick reference guide, setup poster, maintenance sheet, copy/scan software, documentation software, ether touck, USB cable, power cords HP Software and solutions Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <2.9 dB(A) (sleep) Power Consumption Printer: 45 dB(A) (operating), 5.1 B(A) (idle), <3 9 B(A) (sleep); Scanner: 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep) Power Consumption Printer: 45 dB(A) (operating), 5.1 B(A) (idle), <3 9 B(A) (sleep); Sc	Handling	Scanner: Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of
Standard sheets A, B, C, D, E Thickness Up to 31.5 mil Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory Printer: 128 GB (file-processing) ⁴ , Scanner: 8 GB Hard disk Printer: 500 GB self-encrypting; Scanner: 256 GB Connectivity Interfaces Printer: 60 GB self-encrypting; Scanner: 256 GB Connectivity Interfaces Printer: 60 GB self-encrypting; Scanner: 256 GB Connectivity Interfaces Printer: 60 GB self-encrypting; Scanner: 256 GB Connectivity Interfaces Printer: 60 GB self-encrypting; Scanner: 256 GB Connectivity Interfaces Printer: 60 GB self-encrypting; Scanner: 256 GB Connectivity Interfaces Printer: 60 GB self-encrypting; Scanner: 256 GB Connectivity Printer: 70 GB self-encrypting; Scanner: 256 GB Connectivity Printer: 80 GB self-encrypting; Scanner: 256 GB Connectivity Printer: 80 GB self-encrypting; Scanner: 8 GB BB 2.0 certified interface for direct printing from USB flash drive; Scanner: 6 GB self-encrypting; Scanner: 13 O W (Feedy); Scanner: 6 GB self-encrypting; Scanner: 13 O W (Feedy); Scann	Roll size	11 to 44-in (279 to 1118-mm)
Thickness Up to 31.5 mil Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory Printer: 128 GB (fille-processing) ⁶ ; Scanner: 256 GB Hard disk Printer: 500 GB self-encrypting, Scanner: 256 GB Connectivity Interfaces Printer: Gigabit Ethernet (1000Base-17), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-17), USB 3.1 gen 1 (3+1) and USB 2.0 (1) rear Adobe PostScript 3, Adobe PDF 1.7, TiFF, PEG, CALS GA, HP-GL/2, HP-RTL Drivers Printer: Raster and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Scanner: Windows drivers for compatible HP PageWide XL and HP DesignJet Printers Dimensions (W x D x H) Printer Printer: 7.0 s x 27.4 x 39.3 in (1802 x 695 x 998 mm) Scanner: 60 x 37 x 65 in (1530 x 993 x 1660 mm) Shipping 77 x 30 x 50 in (1950 x 766 x 1260 mm) Weight Printer: Printer: 211 lb (96 kg) Scanner: 157 lb (71 kg) Shipping 511 lb (232 kg) What's in the box Printer: HP DesignJet 26dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter, quick reference guide, setup poster, power cord: Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, setup poster, power cord: Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, setup poster, power cord: Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, setup poster, power cord: Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, setup poster, power cord: Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, setup poster, power cord: Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, setup poster, power cord: Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), guick reference guid	Sheet size	8.3 x 11 to 44 x 66 in (210 x 279 to 1118 x 1676 mm)
Applications Banners; Exhibition and event graphics; Light boxes – film; Maps; Orthophotos; Point of sale/display; Posters Memory Printer: 128 GB (file_processing) ⁶ ; Scanner: 256 GB Connectivity Interfaces Printer: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Signation (1000Base-T), USB 3.1 gen 1 (3+1) and USB 2.0 (1) rear Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS GA, HP-GL/Z, HP-RTL Drivers Printer: Raster and PostScript drivers for Windows and macOS PDF driver for Windows B and above Scanner: Windows drivers for compatible HP PageWide XL and HP DesignJet Printers Dirensions (W x D x H) Printer: 7.0.9 x 27.4 x 39.3 in (1802 x 695 x 998 mm) Scanner: 60 x 37 x 65 in (1530 x 930 x 1660 mm) Shipping 77 x 30 x 50 in (1950 x 766 x 1260 mm) Weight Printer Printer: 211 lb (96 kg) Scanner: 157 lb (71 kg) Shipping 511 lb (232 kg) What's in the box Printer: HP DesignJet Z 56dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter, quick reference guide, setup poster, power cord, Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference quide, setup poster, power cord, Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference quide, setup poster, power cord, Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference quide, setup poster, maintenance sheet, copy/scan software, documentation software, Ethernet cable, USB cable, power cords Printer: HP DesignJet Z 56dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter, quick reference guide, setup poster, power cord, Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, setup poster, maintenance sheet, copy/scan software, documentation software, Ethernet cable, USB cable, power cords Pri	Standard sheets	A, B, C, D, E
Memory Printer: 128 GB (file-processing) ⁴ , Scanner: 8 GB Hard disk Printer: 500 GB self-encrypting: Scanner: 256 GB Connectivity Interfaces Printer: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-T), USB 3.1 gen 1 (3+1) and USB 2.0 (1) rear Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, IPEG, CALS GA, HP-GL/2, HP-RTL Drivers Printer: Raster and PostScript drivers for Windows and macOS	Thickness	Up to 31.5 mil
And disk Printer: 500 GB self-encrypting: Scanner: 256 GB Connectivity Interfaces Printer: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-T), USB 3.1 gen 1 (3+1) and USB 2.0 (1) rear Native print languages Adobe PostScript 3, Adobe PDE 1-7, TIFF, JPEG, CALS G4, HP-GU/Z+, HP-RTL Drivers Printer: Raster and PostScript drivers for Windows and mac US	Applications	Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters
Interfaces Printer: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-T), USB 3.1 gen 1 (3+1) and USB 2.0 (1) rear Native print languages Adobe PostScript 3, Adobe PDF 1.7, TiFF, JPEG, CALS G4, HP-GL/Z, HP-RTL Drivers Printer: Raster and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Scanner: Windows drivers for compatible HP PageWide XL and HP DesignJet Printers Dimensions (W x D x H) Printer Printer: 70.9 x 27.4 x 39.3 in (1802 x 695 x 998 mm) Scanner: 60 x 37 x 65 in (1530 x 930 x 1660 mm) Shipping 77 x 30 x 50 in (1950 x 766 x 1260 mm) Weight Printer Printer: 211 lb (96 kg) Scanner: 157 lb (71 kg) Shipping 511 lb (232 kg) What's in the box Printer: 211 DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spinide, 3-in core adapter, quick reference guide, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, media guides, setup poster, maintenance sheet, copy/scan software, documentation software, Ethernet calle, USB cable, power cords Printer drivers, HP Click, HP Web Jetadmin, HP JetAdvantage Security Manager, HP DesignJet Utility including HP Color Center, Hi MPS, integrated software with scan and copy enhancement features Environmental ranges Operating humidity 20 to 80% RH Storage temperature 41 to 95% (5 to 35%C) Operating humidity 20 to 80% RH Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Sound power Printer: 45 dB(A) (operating), 5.1 B(A) (idle), <3.9 B(A) (sleep); Scanner: 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep) Power Consumption Printer: Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), z A max; Scanner: Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), z A max; Scanner: Input voltage (auto rang	Memory	Printer: 128 GB (file-processing) ⁴ ; Scanner: 8 GB
Printer: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive; Scanner: Gigabit Ethernet (1000Base-T), USB 3.1 gen 1 (3+1) and USB 2.0 (1) rear Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Drivers Printer: Rastre and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Scanner: Windows drivers for compatible HP PageWide XL and HP DesignJet Printers Dimensions (W x D x H) Printer: 70.9 x 27.4 x 39.3 in (1802 x 695 x 998 mm) Scanner: 60 x 37 x 65 in (1530 x 930 x 1660 mm) Shipping 77 x 30 x 50 in (1950 x 766 x 1260 mm) Weight Printer: Printer: 211 lb (96 kg) Scanner: 157 lb (71 kg) Shipping 511 lb (232 kg) What's in the box Printer: 41P DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapte, quick reference guide, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, media guides, setup poster, maintenance sheet, copy/scan software, documentation software, Ethernet cable, USB cable, power cords HP Software and solutions Printer drivers, HP Click, HP Web Jetadmin, HP JetAdvantage Security Manager, HP DesignJet Utility including HP Color Center, Hi MPS, integrated software with scan and copy enhancement features Environmental ranges Operating humidity 20 to 80% RH Storage temperature 41 to 95°F (5 to 35°C) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Power Consumption Printer: 6.3 B(A) (operating), 5.1 B(A) (idle), <3.9 B(A)(sleep); Scanner: 6.4 B(A) (operating), <3.9 B(A) (sleep) Power Consumption Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz	Hard disk	Printer: 500 GB self-encrypting; Scanner: 256 GB
Gigabit Ethernet (1000Base-T), USB 3.1 gen 1 (3+1) and USB 2.0 (1) rear	Connectivity	
Printer: Raster and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Scanner: Windows drivers for compatible HP PageWide XL and HP DesignJet Printers Dimensions (W x D x H) Printer	Interfaces	
PDF driver for Windows 8 and above Scanner: Windows drivers for compatible HP PageWide XL and HP DesignJet Printers Dimensions (W x D x H) Printer: 7.0 9 x 27.4 x 39.3 in (1802 x 695 x 998 mm)	Native print languages	Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL
Printer Printer Printer: 70.9 x 27.4 x 39.3 in (1802 x 695 x 998 mm) Scanner: 60 x 37 x 65 in (1530 x 930 x 1660 mm) Weight Printer Printer: 211 lb (96 kg) Scanner: 157 lb (71 kg) Shipping 511 lb (232 kg) What's in the box Printer: HP DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter, quick reference guide, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, media guides, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan documentation software, Ethernet cable, USB cable, power cords HP Software and solutions Printer drivers, HP Click, HP Web Jetadmin, HP JetAdvantage Security Manager, HP DesignJet Utility including HP Color Center, HI MPS, integrated software with scan and copy enhancement features Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <2.9 dB(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 33 W (ready); <1 W (sleep) Printer: Input voltage (auto ranging); 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: input voltage (auto ranging); 100-	Drivers	PDF driver for Windows 8 and above
Scanner: 60 x 37 x 65 in (1530 x 930 x 1660 mm) Shipping 77 x 30 x 50 in (1950 x 766 x 1260 mm) Weight Printer Printer 211 lb (96 kg) Scanner: 157 lb (71 kg) Shipping 511 lb (232 kg) What's in the box Printer: HP DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter, quick reference guide, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, media guides, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan douchscreen (panel PC), quick reference guide, media guides, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan douchscreen (panel PC), quick reference guide, media guides, setup poster, maintenance sheet, copy/scan software, documentation software, Ethernet cable, USB cable, power cords HP Software and solutions Printer drivers, HP Click, HP Web Jetadmin, HP JetAdvantage Security Manager, HP DesignJet Utility including HP Color Center, HI MPS, integrated software with scan and copy enhancement features Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Sound power Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 33 W (ready); <1 W (sleep) Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 HZ (±3 Hz), 2 A max; Scanner: input voltage (auto ranging): 100-	Dimensions (W x D x H)	
Weight Printer: 211 lb (96 kg) Scanner: 157 lb (71 kg) Shipping 511 lb (232 kg) What's in the box Printer: HP DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter, quick reference guide, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, media guides, setup poster, maintenance sheet, copy/scan software, documentation software, Ethernet cable, USB cable, power cords HP Software and solutions Printer drivers, HP Click, HP Web Jetadmin, HP JetAdvantage Security Manager, HP DesignJet Utility including HP Color Center, Hi MPS, integrated software with scan and copy enhancement features Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 33 W (ready); <1 W (sleep) Printer: Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: input voltage (auto ranging): 100-	Printer	
Printer: 211 lb (96 kg) Scanner: 157 lb (71 kg) Shipping 511 lb (232 kg) What's in the box Printer: HP DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter, quick reference guide, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, media guides, setup poster, maintenance sheet, copy/scan software, documentation software, Ethernet cable, USB cable, power cords HP Software and solutions Printer drivers, HP Click, HP Web Jetadmin, HP Jetadvantage Security Manager, HP DesignJet Utility including HP Color Center, HI MPS, integrated software with scan and copy enhancement features Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 33 W (ready); <1 W (sleep) Printer: Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: input voltage (auto ranging): 100-	Shipping	77 x 30 x 50 in (1950 x 766 x 1260 mm)
Scanner: 157 lb (71 kg) Shipping 511 lb (232 kg) What's in the box Printer: HP DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter, quick reference guide, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, media guides, setup poster, maintenance sheet, copy/scan software, documentation software, Ethernet cable, USB cable, power cords HP Software and solutions Printer drivers, HP Click, HP Web Jetadmin, HP JetAdvantage Security Manager, HP DesignJet Utility including HP Color Center, HI MPS, integrated software with scan and copy enhancement features Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 33 W (ready); <1 W (sleep) Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: input voltage (auto ranging): 100-	Weight	
What's in the box Printer: HP DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter, quick reference guide, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, media guides, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, media guides, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stan touchscreen (panel PC), quick reference guide, media guides, setup poster, power cord; HP Software and solutions Printer drivers, HP Click, HP Web Jetadmin, HP JetAdvantage Security Manager, HP DesignJet Utility including HP Color Center, HI MPS, integrated software with scan and copy enhancement features Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Sound power Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 33 W (ready); <1 W (sleep) Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 HZ (±3 Hz), 2 A max; Scanner: input voltage (auto ranging): 100-	Printer	
HP Software and solutions Printer drivers, HP Click, HP Web Jetadmin, HP JetAdvantage Security Manager, HP DesignJet Utility including HP Color Center, Hi MPS, integrated software with scan and copy enhancement features Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Found power Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 33 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 33 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 33 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 30 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 30 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 30 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 30 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 30 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 30 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 30 W (ready); <10.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W	Shipping What's in the box	Printer: HP DesignJet Z6dr 44-in PostScript Printer with V-Trimmer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter, quick reference guide, setup poster, power cord; Scanner: HP HD Pro 2 42-in Scanner, stant touchscreen (panel PC), quick reference guide, media guides, setup poster, maintenance sheet, copy/scan software,
Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Sound power Printer: 6.3 B(A) (operating), 5.1 B(A) (idle), <3.9 B(A)(sleep); Scanner: 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <1 W (sleep) Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: input voltage (auto ranging): 100-	HP Software and solutions	Printer drivers, HP Click, HP Web Jetadmin, HP JetAdvantage Security Manager, HP DesignJet Utility including HP Color Center, HF
Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (idle), <22 dB(A) (idle), <3.9 B(A) (sleep); Scanner: 6.4 B(A) (operating), <3.9 B(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <1.0 W (sleep) Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-	Environmental ranges	· · · · · · · · · · · · · · · · · · ·
Operating humidity 20 to 80% RH Storage temperature -13 to 131% (-25 to 55%) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Sound power Printer: 6.3 B(A) (operating), 5.1 B(A) (idle), <3.9 B(A)(sleep); Scanner: 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <1 W (sleep) Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-	Operating temperature	41 to 95°F (5 to 35°C)
Storage temperature -13 to 131% (-25 to 55%) Acoustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (idle), <22 dB(A) (idle), <22 dB(A) (idle), <3.9 B(A) (sleep); Scanner: 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <1 W (sleep) Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-	Operating humidity	
Aroustics Sound pressure Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Sound power Printer: 6.3 B(A) (operating), 5.1 B(A) (idle), <3.9 B(A)(sleep); Scanner: 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <1 W (sleep) Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-	Storage temperature	
Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) Sound power Printer: 6.3 B(A) (operating), 5.1 B(A) (idle), <3.9 B(A)(sleep); Scanner: 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <1 W (sleep) Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-	Acoustics	
Sound power Printer: 6.3 B(A) (operating), 5.1 B(A) (idle), <3.9 B(A)(sleep); Scanner: 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep) Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <1 W (sleep) Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-		Printer: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A)(sleep); Scanner: 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep)
Power Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <1 W (sleep) Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-		
Consumption Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <1 W (sleep)		
Requirements Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-	Consumption	Printer: <100 W (printing); <32 W (ready); <0.3 W (<6.5 W with embedded Digital Front End) (sleep); 0.1 W (off); Scanner: 130 W (scanning); 39 W (ready); <1 W (sleep)
	Requirements	Printer: Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max; Scanner: Input voltage (auto ranging): 100-

Certification

Safety	Printer: USA and Canada (CSA certified); Scanner: USA and Canada (UL certified)
Electromagnetic	Printer: Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES); Scanner: Compliance for Class A ITE products: USA (FCC Rules), Canada (ICES)
Environmental	Printer: ENERGY STAR; ErP; WEEE; REACH; EPEAT; Scanner: ENERGY STAR; WEEE; REACH; EPEAT
Warranty	One-year limited hardware warranty

Ordering information

2QX51E	HP DesignJet HD Pro 2 44-in MFP	
Accessories		
1QF38A	HP DesignJet 44-in Take-up Reel	
CN538A	HP DesignJet 3-in Core Adapter	
P7V13A	HP Pro Scanner Output Delivery Tray	
Q6709A	HP DesignJet 44-in Spindle	

Original HP printing supplies

P2V25A	HP 746 DesignJet Printhead
P2V78A	HP 746 300-ml Magenta DesignJet Ink Cartridge
P2V79A	HP 746 300-ml Yellow DesignJet Ink Cartridge
P2V80A	HP 746 300-ml Cyan DesignJet Ink Cartridge
P2V81A	HP 746 300-ml Chromatic Red DesignJet Ink Cartridge
P2V82A	HP 746 300-ml Photo Black DesignJet Ink Cartridge
P2V83A	HP 746 300-ml Matte Black Design let Ink Cartridge

Des Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit hp.com/go/OriginalHPinks.

Original HP large format printing materials

HP Universal Instant-dry Satin Photo Paper (FSC® certified)⁵ (Recyclable)⁶ HP Artist Matte Canvas
HP Heavyweight Coated Paper (FSC® certified)⁵ (Recyclable)⁶
HP Everyday Matte Polypropylene (Recyclable)⁶
HP Premium Matte Photo Paper (FSC® certified)⁵ (Recyclable)⁶

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U7UL9E HP 3 year Next Business Day plus DMR Support

U7UM1E HP 5 year Next Business Day plus DMR Support H4518E HP Network Installation Service with Network Setup

U7UM2PE HP 1 year Post Warranty, Next Business Day plus DMR Support

 ${\sf HP} \ {\sf Support} \ {\sf Services} \ {\sf offer} \ {\sf installation} \ {\sf and} \ {\sf extended} \ {\sf support} \ {\sf services} \ ({\sf e.g.}\ 2,3,4,{\sf and}\ 5\ {\sf years}). \ {\sf For} \ {\sf more}$ information, please visit http://www.hp.com/go/cpc

1 Maximum rate of output for color image 100% color coverage. Printed on maximum roll size, with Original HP Vivid Photo links.
2 Except self-adhesive vinyls and non-cuttable medias.
3 Color scanning: A1/D fully-inked color image at 200 dpi, 24-bit RGB. Monochrome scanning: A1/D image with black text graphics at 200 dpi.
4 Based on 4 GB RAM.
5 BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C01533, see http://www.fsc.org and all FSC®-certified products are available in all regions.
6 Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices, or can be returned through the HP Large Format Media take-back program. Recycling programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.



















